

Fig 3



Fig 1



Fig 2



Fig 4



Fig 6



Fig 5


3 digit liquid crystal display (LCD)
S1 S2 S3 S4 S5 S6 S7 S8 S9 COM1 COM2 COM3 E
capacitor
C C
S1 S2 S3
S4 S5 S6
S7 S8 S9
output
commutator
decoder
flash circuit
double voltage circuit
COM1 COM2 COM3
synchronization circuit
counter 1 bit
counter 2 bit
counter 3 bit
oscillator
A
B
in 3
3
anti-bounce circuit
control count's direction
setup
T- 1
T+ 2
switch
1 2
battery

Fig 7



Fig 8



Fig 9



Fig 10



Fig 11



Fig 12



Fig 13



Fig 14



Fig 15



Fig 16



Fig 17



Fig 18



Fig 19



Fig 20



X = Point at which switch closes in electronic counter circuit

Y = Point at which valve opens and medicament begins to dispense

Z = Total canister travel

T_V= Tolerance of valve actuation

T_{SW}= Tolerance of trigger seal and switch assembly

LAG = Difference between switch closure and valve opening – aim to reliably minimize

$= ½ (T_V + T_{SW})$

S_{ACT} = Slope or dynamic profile of actuation motion

S_{SW} = Slope or dynamic profile of trigger seal and switch motion

Fig 21

Fig 22a



Valve Closed (Switch Open)

Fig 22b



Valve Open (Switch Closed)

Membrane Switch



Fig 23a

Contact Switch



Fig 23b



Fig 24a



Fig 24b



Fig. 25